



halton chemical inc.
QUALITY BLENDERS SINCE 1962

- lacquers & related wood coatings
- solvent based & water based products
- adhesives
- coatings
- cleaners
- degreasers
- thinners
- reducers
- epoxies
- polyurethanes
- toll manufacturing
- product development
- product enhancement
- quality control
- warehousing & logistics

SECTION 1 – PRODUCT IDENTIFICATION AND COMPANY IDENTIFICATION

Manufacturer:..... HALTON CHEMICAL INC.
840 APPLEBY LINE, BURLINGTON, ON L7L 2Y7
www.haltonchemical.com

Phone:..... 905-637-3613

Supplier: SCREENTEC CORPORATION
930 WESTPORT CRESCENT, MISSISSAUGA, ON L5T 1G1
www.screentec.ca

Phone:..... 905-670-7042

Emergency Phone: CANUTEC (24H) 1-613-996-6666

Poison Control:..... 800-268-9017

Revision Date:..... February 15, 2017

Print Date:..... February 16, 2017

Version Number:..... 1

Product: T4365 SCREENWASH 902

Product Use: INDUSTRIAL SOLVENT
FOR INDUSTRIAL USE ONLY

SECTION 2 – HAZARDS IDENTIFICATION

Emergency Overview

Target Organs:

Kidney, liver, reproductive, central nervous system, eyes, skin.

WHMIS Classification:

B2 - FLAMMABLE LIQUID
D2B - TOXIC (EYE AND SKIN IRRITANT)
D2A - TOXIC (EMBRYOTOXIC/FETOTOXIC)

GHS Classification:

Flammable Liquids (Cat. 2)
Skin Irritation (Cat. 2)
Eye Irritation (Cat. 2A)
Reproductive Toxicity (Cat. 2)
Specific Target Organ Toxicity- Single Exposure (Cat. 3) - Central Nervous System
Specific Target Organ Toxicity - Repeated Exposure (Cat. 2) - Liver, kidney
Aspiration Hazard (Cat. 1)

Safety Data Sheet - T4365 SCREENWASH 902

GHS Label Elements, including precautionary statements:

Pictogram:



Signal Word:..... **Danger**

Hazard Statement(s):

H225: Highly flammable liquid and vapour

H315: Causes skin irritation

H319: Causes serious eye irritation

H361: Suspected of damaging fertility or the unborn child

H336: May cause drowsiness or dizziness

H373: May cause damage to organs through prolonged or repeated exposure

H304: May be fatal if swallowed and enters airways

Precautionary Statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking

P233: Keep container tightly closed

P240: Ground/bond container and receiving equipment

P241: Use explosion-proof electrical/ventilating/lighting/equipment

P242: Use only non-sparking tools

P243: Take precautionary measures against static discharge

P264: Wash skin thoroughly after handling

P202: Do not handle until all safety precautions have been read and understood

P280: Wear protective gloves/protective clothing/eye protection/face protection

P362+364: Take off contaminated clothing and wash it before reuse

P260: Do not breathe dust/fume/gas/mist/vapours/spray

P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P332+313: If skin irritation occurs: Get medical advice/attention

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P337+313: If eye irritation persists get medical advice/attention

P308+313: IF exposed or concerned: Get medical advice/attention

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P314: Get Medical advice/attention if you feel unwell

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331: Do NOT induce vomiting

P403+235: Store in a well ventilated place. Keep cool

P370+378: In case of fire: Use foam, water fog, dry chemical and/or carbon dioxide to extinguish

P501: Dispose of contents/container to comply with local, provincial, state, and federal regulations.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	%
Acetone	67-64-1	22.00-24.00
Isopropyl Alcohol	67-63-0	5.00-8.00
Diacetone Alcohol	123-42-2	8.00-10.00
Toluene	108-88-3	60.00-62.00

Refer to Section 8 for Occupational Exposure Guidelines.

SECTION 4 – FIRST-AID MEASURES

Inhalation:

This product is (extremely) flammable. Take proper precautions (e.g. remove any sources of ignition). If breathing is stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Avoid mouth-to-mouth contact by using mouth guard or shields. Quickly transport victim to an emergency care facility.

Ingestion:

Never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. Have victim drink 60-240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim rinse mouth with water again. Obtain medical advice.

Eyes:

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, do not delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.

Skin:

Remove contaminated clothing, shoes, and leather goods (e.g. watchbands, belts). Flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, repeat flushing. Obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

Note to Physician:

Treatment should be based on sound judgement of physician and individual reactions of patient.

SECTION 5 – FIRE-FIGHTING MEASURES

Extinguishing Media:

Foam, water spray, dry chemical, carbon dioxide.

Special Fire Fighting Procedures:

Use water spray to cool fire-exposed containers or structures.

Unusual Fire and Explosion Hazards:

Vapours from this product are heavier than air and may travel to a source of ignition and flash back causing explosion and fire. Never use welding or cutting torch on, or near drum (even empty) as product (even residue) can ignite explosively. All containers, including pails, drums, tank cars & trucks should be grounded and/or bonded when material is transferred.

Hazardous Combustion Products:

Carbon monoxide and/or carbon dioxide.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Dyke and contain spills. Do not let product enter drains.

Methods and Materials for Containment and Clean Up:

Contain and/or dyke spills. Absorb with inert material, place in a suitable container. Report and dispose of according to local regulations.

SECTION 7 – HANDLING AND STORAGE

Storage:

Keep container tightly closed in a dry and well-ventilated area. Containers which are opened must be carefully resealed and kept upright to prevent leakage and evaporation.

Handling:

Use in a well ventilated area. Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof tools, equipment, and ventilation system. Keep away from sources of ignition. Take measures to prevent the build-up of electrostatic charge. Always ground and bond containers.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Threshold Limit Value:..... 20 ppm ACGIH est. (Toluene)

Engineering Controls:

Use local, mechanical, explosion proof exhaust and/or ventilation system to avoid exposure and vapour accumulation.

Personal Protective Equipment:

Respiratory Protection:

Where risk assessment shows air-purifying respirators are appropriate, use an approved respirator for the concentration and type of hazardous materials in the workplace. Use respirators and components tested and approved under the appropriate government standards. Use respirators as backup to engineering controls if necessary.

Hand Protection:

Handle with gloves to minimize skin contact. Inspect gloves prior to use. Use proper glove removal technique (without touching the glove's outer surface) to avoid skin contact with product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash hands thoroughly.

Eye Protection:

Safety glasses and/or face shield. Use equipment for eye protection tested and approved under the appropriate government standards.

Safety Data Sheet - T4365 SCREENWASH 902

Protective Clothing:

Impervious clothing, flame retardant, antistatic protective clothing. The type of protective equipment should be selected according to the concentration and amount of hazardous materials at each specific workplace.

Additional Measures:

Handle in accordance with good industrial hygiene and safety practices. Wash hands before breaks and at the end of the workday.

SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

Physical State: Liquid
Appearance/Odour: Clear, colourless with solvent odour
Odour Threshold: Not available
Vapour Density (AIR=1): Heavier than air
Boiling Point: 56°C est. (Acetone)
Melting/Freezing Point: Not available
Vapour Pressure: Not available
Evaporation Rate: Slower than butyl acetate
Specific Gravity: 0.844
Solubility in Water: Soluble
Coeff. Water/Oil Dist.: Not available

Flashpoint: -16.99°C T.C.C. est. (Acetone)
Autoignition Temp: 425°C est. (Isopropyl Alcohol)
Upper Flammable Limit: 13.0% est. (Acetone)
Lower Flammable Limit: 1.2% est. (Toluene)

SECTION 10 – STABILITY AND REACTIVITY

Stability:

Stable.

Hazardous Decomposition Products:

Carbon monoxide and/or carbon dioxide.

Materials to Avoid:

Strong oxidizing agents, strong acids and bases, reducing agents, phosphorous oxychloride, aluminum, halogenated compounds.

Hazardous Reactions:

No data.

Conditions to Avoid:

Heat, flames and sparks.

SECTION 11 – TOXICOLOGICAL INFORMATION

HAZARDOUS INGREDIENT	LD50	LC50	HRS
Acetone	5800 mg/kg	30000 ppm	4
Isopropyl Alcohol	5045 mg/kg	30 mg/L	4
Diacetone Alcohol	4000 mg/kg	7.23 mg/L	4
Toluene	>5580 mg/kg	12500-28800 mg/m3	4

Safety Data Sheet - T4365 SCREENWASH 902

Skin corrosion/irritation:

Rabbit - skin irritation - 24 hour

Serious eye damage/irritation:

Rabbit - eye irritation - 24 hour

Respiratory or skin sensitization:

Not classified as a sensitization hazard.

Germ cell mutagenicity:

Not expected to be mutagenic in humans.

Carcinogenicity:

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity:

Excessive exposure during pregnancy may be hazardous to the developing fetus. Experiments have shown reproductive toxicity effects in male and female lab animals.

Teratogenicity:

May cause teratogenic/embryo toxic effects at high doses.

Specific target organ toxicity (single exposure):

May cause central nervous system depression.

Specific target organ toxicity (repeated exposure):

May cause liver and/or kidney effects.

Aspiration hazard:

Classified as an aspiration hazard.

Potential Health Effects:**Inhalation:**

Prolonged exposure to high vapour concentration can lead to central nervous system depression. signs of this include headache, nausea, dizziness, blurred vision and incoordination.

Ingestion:

Causes irritation, a burning sensation of the mouth, throat and abdominal pain. May cause central nervous system (cns) depression, dizziness, headache, diarrhea, nausea and vomiting. Aspiration of material into the lungs can cause chemical pneumonitis.

Skin:

Prolonged and repeated contact can cause defatting and drying of the skin resulting in irritation and dermatitis.

Eyes:

Irritating, may cause a burning sensation, redness, swelling, and/or blurred vision.

Signs and Symptoms of Exposure:

Can cause central nervous system effects, including dizziness, weakness, fatigue, nausea, headache, blurred vision and possible unconsciousness.

Synergistic effects:

Not available.

Additional information:

Prolonged or repeated exposure may cause liver and kidney effects and central nervous system depression. Solvent abusers exposed to high doses of aromatic solvents show signs of hearing loss as well as damage to the brain, liver and kidney.

SECTION 12 – ECOLOGICAL INFORMATION

Environmental Fate and Distribution:

Prevent from entering drains, sewers, streams or other bodies of water. If runoff occurs, notify authorities as required.

Aquaticity:

LC50 (Oncorhynchus Mykiss) 7.63 mg/L, 96H est. (Toluene)

LC50 (Oncorhynchus Mykiss) 5540 mg/L, 96H est. (Acetone)

Persistence and degradability:

No data.

Bioaccumulative potential:

No data.

Mobility in soil:

No data.

Other adverse effects:

May be toxic to aquatic life.

SECTION 13 –DISPOSAL CONSIDERATIONS

Waste disposal:

Collect and reclaim or dispose in sealed containers at a licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Dispose of in accordance with all applicable regulations.

Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since empty containers may retain product residue, follow any label warnings even after container is emptied.

SECTION 14 – TRANSPORTATION INFORMATION

TDG Classification (Ground Only):CLASS 3 UN1993 II

Proper Shipping Name (Ground Only):FLAMMABLE LIQUIDS N.O.S. (ACETONE)

A scientific determination was concluded based on formulation ingredients on February 15, 2017 to define the Transportation of Dangerous Goods Classifications.

SECTION 15 - REGULATIONS

This material is included on the DLS (Canadian Domestic Substance List) under the CEPA (Canadian Environmental Protection Act).

This material has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This material meets TSCA (Toxic Substances Control Act) inventory requirements.

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

SECTION 16 – OTHER INFORMATION

LEGEND TO ABBREVIATIONS:

CAS: CHEMICAL ABSTRACT SERVICES
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
LC: LETHAL CONCENTRATION
LD: LETHAL DOSE
TDG: TRANSPORTATION OF DANGEROUS GOODS
TWA: TIME WEIGHTED AVERAGE
VOC: VOLATILE ORGANIC COMPOUND

The information contained in this form is based on data from sources considered to be reliable but Halton Chemical Inc. does not guarantee the accuracy or completeness thereof. The information is provided as a service to persons purchasing or using the material to which it refers and Halton Chemical Inc. expressly disclaims all liability for loss or damage, including consequential loss, or for injury to persons (including death) arising directly or indirectly from reliance upon the information or use of the material.