

TECHNICAL DATA SHEET

KIWO DEGREASER 1:20

1. DESCRIPTION

KIWO DEGREASER 1:20 is a highly efficient cleaning and degreasing concentrate for printing screens. It is suitable for all mesh types and prevents pinholes and irregularities in the coating. KIWO DEGREASER 1:20 solutions emulsify dirt and grease thus making them water soluble. A strong foaming action accelerates the degreasing process and is an aid in determining rinsing. KIWO DEGREASER 1:20 is formulated to be diluted with water at a ratio of 1:20, but can be used in different ratios to adapt to the level of contamination.

2. APPLICATION

Mix 1 part KIWO DEGREASER into 20 parts of water. To avoid foaming pour the degreaser concentrate into the water, not the water into the concentrate.

Squirt or spray the solution onto the wet screen and brush from both sides using a Nylon bristle brush until the foam is distributed equally over the screen. Then rinse with water until it runs free of foam. After drying, the screen is ready to be coated.

It is recommended to degrease the screens as shortly before the screen is coated as possible, to eliminate contamination of the clean screen.

KIWO DEGREASER 1:20 can also be used prior to decoating or reclaiming to remove oily residues from solvents and inks.

3. PHYSICAL DATA

Color:	Red - orange
Consistency:	Liquid
Shelflife:	1 year at 68º Fahrenheit (20º Celsius)
Flash point:	Not applicable
TLV:	Not applicable
VOC:	None
pH value:	9
HMIS rating:	Health - 1 Flammability - 0 Reactivity - 0

4. PERSONAL PROTECTION

It is recommended to wear protective glasses and gloves. See Material Safety Data Sheet for additional information.

5. ENVIRONMENTAL PROTECTION

KIWO DEGREASER 1:20 can be eliminated through biological decomposition in adapted waste water treatment plants. The working solution can generally be emptied into the drains. Consult local authorities for local regulations.

6. PACKAGING

1 quart, 1 gallon, 5 gallon containers

7. ADDITIONAL INFORMATION

For additional product information, please visit our web site at <u>www.kiwo.com</u>. For further information contact your KIWO distributor or KIWO direct.

Thank you for choosing KIWO.

Version 8/98



KIWO, Inc. 1929 Marvin Circle P.O. Box 1009 Seabrook, TX 77586 Phone: 281-474-9777 (1-800-KIWO-USA) Fax: 281-474-7325 USA KISSEL & WOLF GmbH In den Ziegelwiesen 6 D-69168 Wiesloch Phone: +49-6222-578-0 Fax: +49-6222-578-100 Germany KISSEL & WOLF Australia PTY. Ltd. Unit 12, 23 Bunney Road Oakleigh South, VIC 3167 Phone: +61-3-551-6887 Fax: +61-3-551-5532 Australia

LIMITED WARRANTY: Due to the inability of KIWO to anticipate or control conditions whereby KIWO products will be employed, KIWO does not represent or guarantee that any KIWO product is fit for a particular purpose. Kiwo products should be tested by users to determine suitability for a particular purpose. KIWO disclaims responsibility for claims and damages beyond replacement of any defective KIWO product. There are no warranties which extend beyond the description on the face hereof